


### Event Diversion Systems

EC2C1J Page 1 of 2

## **Component Specification**



MATERIALS OF

Enclosure – Thermal Plastic

CABLE GLAND

Not Applicable



#### Event Diversion Systems

# **Component Specification**

EC2C1J Page 2 of 2

Not Applicable



Bracket type with 4- ¼" holes

ELECTRICAL

Single phase incoming power 120 VAC 5 Amp, SIEMENS LOGO Pre-programmed controller 24 VAC control voltage Heavy duty oil tight indicator lights - 22MM LED full voltage type 1 - GREEN NORMAL INDICATOR 1 - RED EVENT INDICATOR Heavy duty oil tight switches (22MM) 1 - TEST SWITCH 1 - EVENT RESET SWITCH Control quick blow fuse valve, incoming power & indication - 120:24 VAC TRANSFORMER UL 508 LISTED ANTI-CONDENSATION HEATER - 6 WATT STRIP HEATER Controls 1 – 4" PVC full port Flanged Ball Valve

MECHANICAL

**Top Hinged Panel Front** 

CERTIFICATIONS

UL 508 Listed NEMA 4X

#### **SPECIAL NOTES**

The system comes with an automatic exerciser that will automatically fully open and fully close the valve every (7) days if an event has not occurred to keep the system in good working order. The System comes with in-travel indication. If the valve is not fully open or fully closed the GREEN and RED light will blink alternately. In addition this indication will also serve to indicate if the system has a problem.

**ATTITUDE SYSTEMS** 

WWW.ATTITUDESYSTEMS.COM

PHONE (714) 880-9992