

## **Event Diversion Systems**

EC2G2L Page 1 of 2

## Component Specification

COMPONENT DESCRIPTION

Control Panel - The control panel comes with (2) lights (one Green NORMAL and one Red Event) and (2) push buttons (one TEST and one RESET). The panel will continuously monitor the 2" Flow Switch for use (an event). When an EVENT happens the system will go from NORMAL MODE to EVENT MODE. Once the EVENT has ended the system will return to NORMAL MODE. The System can be set for valve normally open or closed. The amount of delay before an event is detected and the time before the systems automatically returns after an EVENT can both be set.

**MANUFACTURER** 

Attitude Systems, LLC (714) 880-9992 5192 Bolsa Avenue Suite 6 Huntington Beach, CA 92649



**WARRANTY** 

3 Years Limited

**PHOTOGRAPH** 



**DIMENSIONS** 

10" X12" X 6" - 10 LBS

MATERIALS OF CONSTRUCTION

Enclosure - Thermal Plastic

**CABLE GLAND** 

Not Applicable



## **Event Diversion Systems**

EC2G2L Page 2 of 2

## **Component Specification**

**CABLE** 

Not Applicable

MOUNTING/END CONFIGURATION

Bracket type with 4- 1/4" holes

**ELECTRICAL** 

Single phase incoming power 120 VAC 10 Amp,
SIEMENS LOGO Pre-programmed controller 24 VAC control voltage
Heavy duty oil tight indicator lights - 22MM LED full voltage type
1 - GREEN NORMAL INDICATOR 1 - RED EVENT INDICATOR
Heavy duty oil tight switches (22MM) 1 - TEST SWITCH 1 - EVENT RESET SWITCH
Control quick blow fuse valve, incoming power & indication - 120:24 VAC TRANSFORMER UL
508 LISTED ANTI-CONDENSATION HEATER - 6 WATT STRIP HEATER
Controls 1 – 8" 316SS 3-Way Flanged Ball Valve

**MECHANICAL** 

Top Hinged Panel Front

**CERTIFICATIONS** 

UL 508 Listed NEMA 4X

**SPECIAL NOTES** 

The system comes with an automatic exerciser that will automatically fully open and fully close the valve every (7) days if an event has not occurred to keep the system in good working order. The System comes with in-travel indication. If the valve is not fully open or fully closed the GREEN and RED light will blink alternately. In addition this indication will also serve to indicate if the system has a problem.