



Event Diversion Systems

Component Specification

COMPONENT DESCRIPTION

Die cast aluminum housing, Incandescent or florescent vapor proof remote RED indicating beacon. Comes with 100 feet of 18/3 jacketed conductor cable

MANUFACTURER

CONFIGURED BY
Attitude Systems,LLC
5192 Bolsa Ave
Suite 6
Huntington Beach, CA 92649
(714) 880-9992

RAB Lighting:
170 Ludlow Avenue
Northvale, NJ 07647
888- RAB-1000



WARRANTY

1 Year

PHOTOGRAPH



DIMENSIONS

7-1/8" Wide at top
9-5/8" Tall
5-3/8" wide Bottom
4.1 LBS

MATERIALS OF CONSTRUCTION

Threaded glass globes fit RAB and other standard Vaporproof fixtures and Lawn Lights

Die cast aluminum one piece guard with distinctive flat bottom for contemporary look. Machined threads for smooth fit. A headless set screw is provided to lock guard in place.

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. incandescent lamp A21

CABLE GLAND

1/2" NPT Nylon moisture resistant IP68 strain relief - For 0.62" max diameter cord



Event Diversion Systems

Component Specification

CABLE

100 Feet SJOOW 18 gauge 2 conductor cable stranded fully annealed copper, Jacket Black, Conductor colors 1- Black 1- White Jacket temperature range -40 +90C High Resistance to UV, Oil and Moisture

MOUNTING/END CONFIGURATION

Wall bracket plus junction box with sturdy mounting lugs

ELECTRICAL

Lamp Type A19
Lamp Wattage Max 100

MECHANICAL

NA

CERTIFICATIONS

UL Listing:
Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gase

SPECIAL NOTES

Red Globe to mimic red indicating light on STORMController